



Feature:

By using the high performance sensor, image is clear, delicate and high performance sensor, image is clear, delicate;
 Support IR-CUT dual filter switch, day and night to achieve monitoring, color is not partial color distortion;
 Analog AHD /CVI/TVI and CVBS video output;
 Support for OSD menu options, can be freely adjusted image, function;
 The transmission distance is 500 meters;
 Support the ultra low illumination;
 Support automatic electronic shutter function, adapt to different monitoring environment;
 Waterproof design IP66, reliability;
 Million pixel HD video transmission of low cost, long distance, no delay, high efficiency, anti-jamming and easy to implement;
 More compatible, able to match AHD /CVI/TVI DVR But also Standalone 960H DVR
 Easy installation & operation, as same as analog CCTV system
 With Bracket for optional
 More acceptable, lower price than analog surveillance system
 NO Delay, Real time Display

Specification

Model No.	NST-ATC9962S
Camera Type	HD Car Camera
Resolution	2.0 Mega Pixel
Main Chip	High performance XM330 DSP processor
Image Sensor	1/3" CMOS Sensor
Signal System	PAL/NTSC
Video Standard	Follow AHD /CVI/TVI and CVBS Standard
Video Output	1CH AHD/CVI/TVI HD/CVBS Standard Singal Output(Switchable)
Max Transmission Distance	Common 75-3lines can be up to 500m
Lens size	Fixed 3.6mm
Minimum Illumination	0.000LUX/F1.2(Led on)
IR-CUT	Auto switch
LED	18pcs IR LEDs
IR Distance	15m
Shutter Speed	4/25s-1/45,000s
BLC	Off/Low/Medium/High/Highest
White Balance	Auto White Balance
HLC	Support
Operation Temperature	-10°C~65°C
Power Supply	DC12V