



Model No.		NST-IPC6725
Camera Type		Bullet IP Camera
System		Embedded RTOS design
Camera	Effective Pixels	5.0 Mega Pixels
		Main stream:2592H*1944V; Sub stream:704*576
	Frames Rates	PAL:20fps(2592H*1944V)
		NTSC:30fps(2592H*1944V)
	Image Sensor	1/2.8" SONY CMOS Sensor
		5.0 megapixel resolution (2592H*1944V)
	DSP	Dual core 32-bit DSP
		(HI3516E)
	Min. Illumination	Color 0.001Lux@F1.2
		B/W 0.0001 Lux@F1.2
Adjust Parameters	DWDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.	
Video	Compression	H.265 Main profile
	Stream	support dual stream,AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable
	Frame Rates	support 1~20fps adjust
Audio	Input and output	1ch input(micphone),1ch output(Speaker&micphone) Optional
	Compression	G.711 compression,support two-way audio intercom,support audio and video synchronized output
Alarm	Types	Motion Detection, Video Blind , Video Loss
Network	WEB Browser	Support WEB remote config(IE, Safari, Google Chrome, Firefox etc.)
	Smart Phone	mobile remote Monitoring (iPhone,Android,....)

	CMS Software	Uniform CMS Software(multiple devices management system)
	Cloud P2P	www.enster.com,MYEYE platform and other program,Offer SDK
	Network	1 * RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
	ONVIF	Support (ONVIF 2.4)
	POE	Support(optional)
	WIFI	N/A
General	Language	20 kinds of languages such as English, Finnish, French, German, Greek,Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, S-Chinese, T-Chinese and Turkish
	IR Cut Filter	Set of double light switch IR-CUT filter
	Lens Mount	Board Lens 3.6mm
	Infrared Luminary	36pcs IR LED
	Infrared Wavelength	850nm
	Illuminate Distance	30m
	Waterproof Criterion	IP 66
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)
	Supplied Voltage	DC12V/PoE(802.3af/820.3at)
	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for enviroment lower than -20°)
	Weight	0.6kg