



## NVR-7509H

9 CH 4K IP Camera Input NVR

Support access of multiple XM smart front-end devices with human detection and face detection function.

Support HDMI /VGA HD output;

Support ONVIF;

access third party;

Support VGA, HDMI full HD output simultaneously;

Support ONVIF; access third party;

Support Web, CMS, center platform management software XMEYE, provide SDK development;

Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;

Support various mobile monitoring (iPhone, Android);

Remote Access, With DNS (ARSP),easy to monitor remotely;

Model No.		NST-7509H
System	Main processor	XM8536D
	Operating system	Embedded LINUX operating system
	System resource	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operation interface	16-bit true color graphic menu operation interface, support mouse operation
	Display screen	1/2/4/6/8/9
Video	Video input (IP)	9*4K Unreal-time(Access bandwidth 60Mbps)
	Video standards	PAL(625TVL,50f/s);NTSC(525TVL,60f/s)
	Video compression	H.265A1/H.265+(compatible H.265/H.264)
	Display quality	Max:1080P
	Playback quality	4K/5M/4M/3M/1080P
	Decode	1ch4k/1ch5M/1ch4M/2ch3M/3ch1080P
	Motion detection	Depend on camera

Audio	Audio compression	G711A
	intercom	support
Record and playback	Record mode	Manual>Alarm>Video Detection>Continuous
	Local playback	1ch4k/1ch5M/1ch4M/2ch3M/3ch1080P
	Search mode	search by Time/calendar/event/channel
Storage and back up	Record Storage	HDD 、 network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
Interface	Video output	1ch HDMI HD output(can be extended to support VGA)
	Audio I/O	1/1(3.5mm)
	Alarm I/O	0/0
	Network interface	1* 10M/100M Adaptive Ethernet port
	USB interface	2*USB2.0 port
	Hard disk	1* SATA(Up to 14TB for each disk)
other	PTZ control	Control PTZ device by network
	ONVIF	Available
	Power supply	12V /2 A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C- + 55°C , Humidity:10% - 90%RH , Atm:86kpa - 106kp
	Dimension	L250*W220*H45MM
	Weight	1.2KG