



Model No.		NST-IPH6852-FC
Camera Type		Bullet IP Camera
System		Embedded RTOS design
Camera	Effective Pixels	3.0 Mega Pixels
		Main stream:3.0MP(2045H*1536V);
		Sub stream:704*576
	Frames Rates	PAL:20fps(3.0MP(2045H*1536V))
		NTSC:20fps(3.0MP(2045H*1536V))
	Image Sensor	1/2.7" CMOS Sensor
		2 megapixel resolution
	DSP	Dual core 32-bit DSP (XM535)
Video	Min. Illumination	Color 0.01Lux@F1.2
		B/W 0.01 Lux@F1.2
	Adjust Parameters	DWDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.
Audio	Compression	H.265/H.264 Main profile
	Stream	support dual stream,AVI format
	Bit Rate	support 0.1M ~8Mbps bit rate adjustable
	Frame Rates	support 1~30fps adjust
Alarm	Input and output	1ch input(microphone),1ch output(Speakerµphone) Optional
	Compression	G.711 compression,support two-way audio intercom,support audio and video synchronized output
Network	Types	Motion Detection, Video Blind , Video Loss
	WEB Browser	Support WEB remote config(IE, Safari, Google Chrome, Firefox etc.)
	Smart Phone	mobile remote Monitoring (iPhone,Android,...)
	CMS Software	Uniform CMS Software(multiple devices management system)
	Cloud P2P	www.enster.com,MYEYE platform and other program,Offer SDK
	Network	1 * RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
	ONVIF	Support (ONVIF 2.6)
	POE	Support(optional)
General	WIFI	N/A
	Language	20 kinds of languages such as English, Finnish, French, German, Greek,Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, S-Chinese, T-Chinese and Turkish
	IR Cut Filter	N/A
	Lens Mount	Fixed Lens 3.6mm/F2.0
	Luminary	2pcs Array Yellow Light LED
	Wavelength	590nm
	Illuminate Distance	30m
	Waterproof Criterion	IP 66
	I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)
	Supplied Voltage	DC12V/PoE(802.3af/802.3at)

	Power Consumption	IR On: 600mA max., IR Off: Less than 200mA
	Working Environment	-10°C~+60°C, 10%~90% (Built in Heater being optional added for enviroment lower than -20°)
	Weight	0.6kg