



## NST-NVR7232H

H.265 IP Camera Input 32CH 8MP NVR

Support HDMI 4K output VGA HD output; Support ONVIF; access third party;

Support web, CMS, center platform management software MYEYE, provide SDK development;

Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;

Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, IP searches, Alarm Center, etc.)

Model No.		NST-NVR7232H
System	Main processor	Hi3536C
	Operating system	Embedded LINUX operating system
	System resource	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	Operation interface	16-bit true color graphic menu operation interface, support mouse operation
	Display screen	1/2/4/6/8/9/16/25/32
Video	Video input (IP)	32*4K(Access bandwidth 240Mbps)
	Video standards	PAL(625TVL,50f/s);NTSC(525TVL,60f/s)
	Video compression	H.265A1/H.265+(compatible H.265/H.264)
	Display quality	Max:4K
	Playback quality	4K/5M/4M/3M/1080P
	Decode	4K(1+2)/5M(2+3)/4M(2+5)/3M(3+6)/1080P(5+9)
	Motion detection	Depend on camera
Audio	Audio compression	G711A
	intercom	Unsupport
Record and playback	Record mode	Manual>Alarm>Video Detection>Continuous
	Local playback	4K(1+2)/5M(2+3)/4M(2+5)/3M(3+6)/1080P(5+9)
	Search mode	search by Time/calendar/event/channel

Storage and back up	Record Storage	HDD , network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
Interface	Video output	1ch HDMI HD Output ,1CH VGA Output
	Audio I/O	1/1(3.5MM)
	Alarm I/O	0/0
	Network interface	1* 100M/1000M Adaptive Ethernet port
	USB interface	2*USB2.0 port
	Hard disk	2 SATA(Up to 14TB for each disk)
other	PTZ control	Control PTZ device by network
	ONVIF	Available
	Power supply	12V /4 A
	Power Consumption	<10W(Without HDD)
	Work environment	Temperature:0°C- + 55°C , Humidity:10% - 90%RH , Atm:86kpa - 106kp
	Dimension	L440*W320*H45MM
	Weight	2.2KG